

The NumPy Array: A Structure for Efficient Numerical Computation

Presented at the G-Node Autumn School on
Advanced Scientific Programming in Python,
held in Trento, Italy

Stéfan van der Walt
Stellenbosch University, South Africa

October, 2010

Welcome, introduction, setup

A peek inside
the ndarray

Structured
arrays

Broadcasting

Indexing

Array interface

Wrap up, discussion & exercises

Num-What?

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

Broadcasting

Fancy Indexing

The `__array_interface__`

Discussion, questions & exercises

This talk discusses some of the more advanced NumPy features. If you've never seen NumPy before, you may have more fun doing this tutorial:

<http://mentat.za.net/numpy/intro/intro.html>

You can always catch the rest early next year by reading:

'The NumPy array: a structure for efficient numerical computation'. Stéfan van der Walt, S. Chris Colbert and Gaël Varoquaux. In IEEE Computing in Science Engineering, March/April 2011.

Setup

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

Broadcasting

Fancy Indexing

The `__array_interface__`

Discussion, questions & exercises

```
import numpy as np    # we always use this convention,  
                      # also in the documentation
```

```
print np.__version__ # version 1.4 or greater  
print np.show_config() # got ATLAS/Accelerate/MKL?
```

ATLAS is a fast implementation of BLAS (Basic Linear Algebra Routines). On OSX you have Accelerate; students can get Intel's MKL for free. On Ubuntu, install `libatlas3gf-sse2`.

Make use of **IPython's** powerful features! TAB-completion, documentation, source inspection, timing, cpaste, etc.

The accompanying problem sets are on the Wiki at

<https://portal.g-node.org/python-autumnschool/>

`materials:advanced_numpy`

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

- ndarray
- Data buffers
- Dimensions
- Data-type
- Strides
- Flags
- Base Pointer

Structured arrays

Broadcasting

Fancy Indexing

The `__array__` interface

Discussion, questions & exercises

The NumPy ndarray

Revision: Structure of an ndarray

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

- ndarray
- Data buffers
- Dimensions
- Data-type
- Strides
- Flags
- Base Pointer

Structured arrays

Broadcasting

Fancy Indexing

The `__array_interface__`

Discussion, questions & exercises

Taking a look at `numpy/core/include/numpy/ndarraytypes.h`:

```
typedef struct PyArrayObject {
    PyObject_HEAD
    char *data; /* pointer to data buffer */
    int nd; /* number of dimensions */
    npy_intp *dimensions; /* size in each dimension */
    npy_intp *strides; /* bytes to jump to get
                        * to the next element in
                        * each dimension
                        */
    PyObject *base; /* Pointer to original array
                    /* Decref this object */
                    /* upon deletion. */
    PyArray_Descr *descr; /* Pointer to type struct */
    int flags; /* Flags */
    PyObject *weakreflist; /* For weakreferences */
} PyArrayObject;
```

A homogeneous container

```
char *data;          /* pointer to data buffer */
```

Data is just a pointer to bytes in memory:

```
In [16]: x = np.array([1, 2, 3])
```

```
In [22]: x.dtype
```

```
Out [22]: dtype('int32') # 4 bytes
```

```
In [18]: x.__array_interface__['data']
```

```
Out [18]: (26316624, False)
```

```
In [21]: str(x.data)
```

```
Out [21]: '\x01\x00\x00\x00\x02\x00\x00\x00\x03\x00\x00\x00'
```

Dimensions

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

- ndarray
- Data buffers
- **Dimensions**
- Data-type
- Strides
- Flags
- Base Pointer

Structured arrays

Broadcasting

Fancy Indexing

The `__array_interface__`

Discussion, questions & exercises

```
int nd; /* number of dimensions */
numpy_intp *dimensions; /* size in each dimension */
```

```
In [3]: x = np.array([])
```

```
In [4]: x.shape
```

```
Out [4]: (0,)
```

```
In [5]: np.array(0).shape
```

```
Out [5]: ()
```

```
In [8]: x = np.random.random((3, 2, 3, 3))
```

```
In [9]: x.shape
```

```
Out [9]: (3, 2, 3, 3)
```

```
In [10]: x.ndim
```

```
Out [10]: 4
```

Data type descriptors

```
PyArray_Descr *descr; /* Pointer to type struct */
```

Common types in include int, float, bool:

```
In [19]: np.array([-1, 0, 1], dtype=int)
```

```
Out [19]: array([-1,  0,  1])
```

```
In [20]: np.array([-1, 0, 1], dtype=float)
```

```
Out [20]: array([-1.,  0.,  1.])
```

```
In [21]: np.array([-1, 0, 1], dtype=bool)
```

```
Out [21]: array([ True, False,  True], dtype=bool)
```

Each item in the array has to have the same type (occupy a fixed nr of bytes in memory), but that does not mean a type has to consist of a single item:

```
In [2]: dt = np.dtype([('value', np.int), ('status', np.bool)])
```

```
In [3]: np.array([(0, True), (1, False)], dtype=dt)
```

```
Out [3]:
```

```
array([(0, True), (1, False)],  
      dtype=[('value', '<i4'), ('status', '|b1')])
```

This is called a **structured array**.

Strides

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

- ndarray
- Data buffers
- Dimensions
- Data-type
- **Strides**
- Flags
- Base Pointer

Structured arrays

Broadcasting

Fancy Indexing

The `__array_interface__`

Discussion, questions & exercises

```
numpy_intp *strides;      /* bytes to jump to get */
                          /* to the next element */
```

```
In [37]: x = np.arange(12).reshape((3,4))
```

```
In [38]: x
```

```
Out [38]:
```

```
array([[ 0,  1,  2,  3],
        [ 4,  5,  6,  7],
        [ 8,  9, 10, 11]])
```

```
In [39]: x.dtype
```

```
Out [39]: dtype('int32')
```

```
In [40]: x.dtype.itemsize
```

```
Out [40]: 4
```

```
In [41]: x.strides
```

```
Out [41]: (16, 4) # (4*itemsize, itemsize)
           # (skip_bytes_row, skip_bytes_col)
```

Flags

```
int flags;          /* Flags */
```

```
In [66]: x = np.array([1, 2, 3])
```

```
In [67]: x.flags
```

```
Out [67]:
```

```
  C_CONTIGUOUS : True      # C-contiguous
  F_CONTIGUOUS : True      # Fortran-contiguous
  OWNDATA      : True      # are we responsible for memory handling?
  WRITEABLE   : True      # may we change the data?
  ALIGNED     : True      # appropriate hardware alignment
  UPDATEIFCOPY : False    # update base on deallocation?
```

```
In [68]: z.flags
```

```
Out [68]:
```

```
  C_CONTIGUOUS : False
  F_CONTIGUOUS : False
  OWNDATA      : False
  WRITEABLE   : True
  ALIGNED     : True
  UPDATEIFCOPY : False
```

Base Pointer

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

- ndarray
- Data buffers
- Dimensions
- Data-type
- Strides
- Flags
- Base Pointer

Structured arrays

Broadcasting

Fancy Indexing

The `__array_interface__`

Discussion, questions & exercises

```
PyObject *base; /* Decref this object on deletion */  
/* of the array. For views, points */  
/* to original array. */
```

Trick: Deallocating foreign memory

An ndarray can be constructed from memory obtained from another library. Often, we'd like to free that memory after we're done with the array, but **numpy** can't deallocate it safely. As such, we need to trick numpy into calling the foreign library's deallocation routine. How do we do this? We assign a special object that frees the foreign memory upon object deletion to the ndarray's **base** pointer.

```
PyObject* PyCObject_FromVoidPtr(void* cobj, void (*destr)(void *))
```

Return value: New reference.

Create a `PyCObject` from the `void *` `cobj`. The `destr` function will be called when the object is reclaimed, unless it is `NULL`.

See Travis Oliphant's blog entry at <http://blog.enthought.com/?p=410>.

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

- Reading/writing data

Broadcasting

Fancy Indexing

The `__array_interface__`

Discussion, questions & exercises

Structured arrays

Intro to structured arrays

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

- Reading/writing data

Broadcasting

Fancy Indexing

The `__array_interface__`

Discussion, questions & exercises

Repeating what we said earlier, each item in an array has the same type, but that does not mean a type has to consist of a single item:

```
In [2]: dt = np.dtype([('value', np.int), ('status', np.bool)])
```

```
In [3]: np.array([(0, True), (1, False)], dtype=dt)
```

```
Out[3]:
```

```
array([(0, True), (1, False)],
      dtype=[('value', '<i4'), ('status', '|b1')])
```

This is called a **structured array**, and is accessed like a dictionary:

```
In [3]: x = np.array([(0, True), (1, False)],
                    dtype=dt)
```

```
In [5]: x['value']
```

```
Out [5]: array([0, 1])
```

```
In [6]: x['status']
```

```
Out [6]: array([ True, False], dtype=bool)
```

Structured arrays

Time	Size	Position				Gain	Samples (2048) ...			
		Az	El	Type	ID					
1172581077060	4108	0.715594	-0.148407	1	4	40	561	1467	997	-30
1172581077091	4108	0.706876	-0.148407	1	4	40	7	591	423	
1172581077123	4108	0.698157	-0.148407	1	4	40	49	-367	-565	-35
1172581077153	4108	0.689423	-0.148407	1	4	40	-55	-953	-1151	-30
1172581077184	4108	0.680683	-0.148407	1	4	40	-719	-1149	-491	38
1172581077215	4108	0.671956	-0.148407	1	4	40	-1503	-683	661	149
1172581077245	4108	0.663232	-0.148407	1	4	40	-2731	-281	2327	291
1172581077276	4108	0.654511	-0.148407	1	4	40	-3493	-159	3277	380
1172581077306	4108	0.645787	-0.148407	1	4	40	-3255	-247	3145	385
1172581077339	4108	0.637058	-0.148407	1	4	40	-2303	-101	2079	247
1172581077370	4108	0.628321	-0.148407	1	4	40	-1495	-553	571	107
1172581077402	4108	0.619599	-0.148407	1	4	40	-955	-1491	-1207	-25
1172581077432	4108	0.61087	-0.148407	1	4	40	-875	-3009	-2987	-93
1172581077463	4108	0.602148	-0.148407	1	4	40	-491	-3681	-4193	-175
1172581077497	4108	0.593438	-0.148407	1	4	40	167	-3501	-4573	-250
1172581077547	4108	0.584696	-0.148407	1	4	40	1007	-2613	-4463	-303
1172581077599	4108	0.575972	-0.148407	1	4	40	1261	-2155	-4299	-339
1172581077650	4108	0.567244	-0.148407	1	4	40	1537	-2633	-4945	-367
1172581077702	4108	0.558511	-0.148407	1	4	40	1105	-2701	-6120	-120

Reading data from file

Reading this kind of data can be somewhat troublesome:

```
while ((count > 0) && (n <= NumPoints))
    % get time - I8 [ms]
    [lw, count] = fread(fid, 1, 'uint32');
    if (count > 0) % then carry on
        uw = fread(fid, 1, 'int32');
        t(1,n) = (lw+uw*2^32)/1000;

        % get number of bytes of data
        numbytes = fread(fid, 1, 'uint32');

        % read sMEASUREMENTPOSITIONINFO (11 bytes)
        m(1,n) = fread(fid, 1, 'float32'); % az [rad]
        m(2,n) = fread(fid, 1, 'float32'); % el [rad]
        m(3,n) = fread(fid, 1, 'uint8'); % region type
        m(4,n) = fread(fid, 1, 'uint16'); % region ID
        g(1,n) = fread(fid, 1, 'uint8');

        numsamples = (numbytes-12)/2; % 2 byte integers
        a(:,n) = fread(fid, numsamples, 'int16');
```

Reading data from file

The NumPy solution:

```
dt = np.dtype([('time', np.uint64),
               ('size', np.uint32),
               ('position', [('az', np.float32),
                             ('el', np.float32),
                             ('region_type', np.uint8),
                             ('region_ID', np.uint16)]),
               ('gain', np.uint8),
               ('samples', (np.int16, 2048))])
```

```
data = np.fromfile(f, dtype=dt)
```

We can then access this structured array as before:

```
data['position']['az']
```

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

Broadcasting

- Broadcasting overview (1D)
- Broadcasting overview (2D)
- Broadcasting overview (3D)
- Broadcasting Rules
- Explicit broadcasting

Fancy Indexing

The `__array_interface__`

Discussion, questions & exercises

Broadcasting

Broadcasting overview (1D)

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

Broadcasting

● Broadcasting overview (1D)

● Broadcasting overview (2D)

● Broadcasting overview (3D)

● Broadcasting Rules

● Explicit broadcasting

Fancy Indexing


The `__array_interface__`

Discussion, questions & exercises

Combining of differently shaped arrays without creating large intermediate arrays:

```
>>> x = np.arange(4)
>>> x = array([0, 1, 2, 3])
>>> x + 3
array([3, 4, 5, 6])
```

See the `np.doc.broadcasting` docstring for more detail.



Broadcasting overview (2D)

- Tutorial layout

- Num-What?

- Setup

The NumPy ndarray

Structured arrays

Broadcasting

- Broadcasting overview (1D)

- **Broadcasting overview (2D)**

- Broadcasting overview (3D)

- Broadcasting Rules

- Explicit broadcasting

Fancy Indexing

The `__array_interface__`

Discussion, questions & exercises


```
In [2]: a = np.arange(12).reshape((3, 4))
```

```
In [3]: b = np.array([1, 2, 3])[:, np.newaxis]
```

```
In [4]: a + b
```

```
Out[4]:
```

```
array([[ 1,  2,  3,  4],  
       [ 6,  7,  8,  9],  
       [11, 12, 13, 14]])
```



Broadcasting overview (3D)

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

Broadcasting


- Broadcasting overview (1D)
- Broadcasting overview (2D)
- **Broadcasting overview (3D)**
- Broadcasting Rules
- Explicit broadcasting

Fancy Indexing

The `__array_interface__`

Discussion, questions & exercises

```
>>> x = np.zeros((3, 5))
>>> y = np.zeros(8)
>>> (x[... , None] + y).shape (3, 5, 8)
```



Broadcasting Rules

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

Broadcasting

- Broadcasting overview (1D)
- Broadcasting overview (2D)
- Broadcasting overview (3D)

- **Broadcasting Rules**
- Explicit broadcasting

Fancy Indexing

The `__array_interface__`

Discussion, questions & exercises

The broadcasting rules are straightforward—mostly. Compare dimensions, starting from the last. Match when either dimension is one or None, or if dimensions are equal:

Scalar	2D	3D	Bad
(,)	(3, 4)	(3, 5, 1)	(3, 5, 2)
(3,)	(3, 1)	(, 8)	(, 8)
-----	-----	-----	-----
(3,)	(3, 4)	(3, 5, 8)	XXX

Explicit broadcasting

- Tutorial layout

- Num-What?

- Setup

- The NumPy ndarray

- Structured arrays

- Broadcasting

- Broadcasting overview (1D)

- Broadcasting overview (2D)

- Broadcasting overview (3D)

- Broadcasting Rules

- **Explicit broadcasting**

- Fancy Indexing

- The `__array_interface__`

- Discussion, questions & exercises

```
In [46]: xx, yy = np.broadcast_arrays(x, y)
```

```
In [47]: x = np.zeros((3, 5, 1))
```

```
In [48]: y = np.zeros((3, 5, 8))
```

```
In [49]: xx, yy = np.broadcast_arrays(x, y)
```

```
In [50]: xx.shape
```

```
Out [50]: (3, 5, 8)
```

```
In [51]: np.broadcast_arrays([1, 2, 3], [[1], [2], [3]])
```

```
Out [51]:
```

```
[array([[1, 2, 3],
        [1, 2, 3],
        [1, 2, 3]]),
 array([[1, 1, 1],
        [2, 2, 2],
        [3, 3, 3]])]
```

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

Broadcasting

Fancy Indexing

- Introduction
- Output shape of an indexing op
- Output shape of an indexing op (cont'd)
- Output shape of an indexing op (cont'd)
- Output shape of an indexing op (cont'd)
- Jack's Dilemma
- Jack's Dilemma (cont'd)
- Test setup for Jack's problem
- Solving Jack's problem
- Solution verification

The `__array_interface__`

Discussion, questions & exercises

Fancy Indexing

Introduction

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

Broadcasting

Fancy Indexing

- **Introduction**

- Output shape of an indexing op

- Output shape of an indexing op (cont'd)

- Output shape of an indexing op (cont'd)

- Output shape of an indexing op (cont'd)

- Jack's Dilemma

- Jack's Dilemma (cont'd)

- Test setup for Jack's problem

- Solving Jack's problem

- Solution verification

The `__array_interface__`

Discussion, questions & exercises

Remember that ndarray can be indexed in two ways:

- Using slices and scalars
- Using ndarrays («fancy indexing»)

Simple fancy indexing example:

```
>>> x = np.arange(9).reshape((3,3))
array([[0, 1, 2],
       [3, 4, 5],
       [6, 7, 8]])
```

```
>>> x[:, [1, 1, 2]]
array([[1, 1, 2],
       [4, 4, 5],
       [7, 7, 8]])
```

```
>>> np.array((x[:, 1], x[:, 1], x[:, 2])).T
array([[1, 1, 2],
       [4, 4, 5],
       [7, 7, 8]])
```

Output shape of an indexing op

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

Broadcasting

Fancy Indexing

- Introduction
- Output shape of an indexing op
- Output shape of an indexing op (cont'd)
- Output shape of an indexing op (cont'd)
- Output shape of an indexing op (cont'd)
- Jack's Dilemma
- Jack's Dilemma (cont'd)
- Test setup for Jack's problem
- Solving Jack's problem
- Solution verification

The `__array_interface__`

Discussion, questions & exercises

1. Broadcast all index arrays against one another.
2. Use the dimensions of slices as-is.

```
>>> x = np.array([[0, 1, 2], [3, 4, 5], [6, 7, 8]])
>>> print x
[[0 1 2]
 [3 4 5]
 [6 7 8]]
>>> print x.shape
(3, 3)
>>> idx0 = np.array([[0, 1], [1, 2]]) # row indices
>>> idx1 = np.array([[0, 1]]) # column indices
```

But what would now happen when we do

```
>>> x[idx0, idx1] ???
```

Output shape of an indexing op (cont'd)

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

Broadcasting

Fancy Indexing

- Introduction
- Output shape of an indexing op
- **Output shape of an indexing op (cont'd)**
- Output shape of an indexing op (cont'd)
- Output shape of an indexing op (cont'd)
- Jack's Dilemma
- Jack's Dilemma (cont'd)
- Test setup for Jack's problem
- Solving Jack's problem
- Solution verification

The `__array_interface__`

Discussion, questions & exercises

The dimensions of `idx0` and `idx1` are not the same, but are they «compatible»?

```
>>> print idx0.shape, idx1.shape
(2, 2) (1, 2)
>>> a, b = np.broadcast_arrays(idx0, idx1)
>>> print a
[[0 1]
 [1 2]]
>>> print b
[[0 1]
 [0 1]]
```

Can we now predict the output? Yes.

```
>>> print x
[[0 1 2]
 [3 4 5]
 [6 7 8]]
>>> print x[idx0, idx1]
[[0 4]
 [3 7]]
```

Output shape of an indexing op (cont'd)

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

Broadcasting

Fancy Indexing

- Introduction
- Output shape of an indexing op
- Output shape of an indexing op (cont'd)
- **Output shape of an indexing op (cont'd)**
- Output shape of an indexing op (cont'd)
- Jack's Dilemma
- Jack's Dilemma (cont'd)
- Test setup for Jack's problem
- Solving Jack's problem
- Solution verification

The `__array_interface__`

Discussion, questions & exercises

```
>>> x = np.random.random((15, 12, 16, 3))
```

```
>>> index_one = np.array([[0, 1], [2, 3], [4, 5]])
```

```
>>> index_one.shape
```

```
(3, 2)
```

```
>>> index_two = np.array([[0, 1]])
```

```
>>> index_two.shape
```

```
(1, 2)
```

Predict the output shape of:

```
x[5:10, index_one, :, index_two]
```

Warning! When mixing slicing and fancy indexing, the *order* of the output dimensions are somewhat unpredictable.
Play it safe and don't mix the two!

Output shape of an indexing op (cont'd)

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

Broadcasting

Fancy Indexing

- Introduction
- Output shape of an indexing op
- Output shape of an indexing op (cont'd)
- Output shape of an indexing op (cont'd)
- **Output shape of an indexing op (cont'd)**
- Jack's Dilemma
- Jack's Dilemma (cont'd)
- Test setup for Jack's problem
- Solving Jack's problem
- Solution verification

The `__array_interface__`

Discussion, questions & exercises

```
>>> x = np.random.random((15, 12, 16, 3))
```

```
>>> index_one = np.array([[0, 1], [2, 3], [4, 5]])
```

```
>>> index_one.shape
```

```
(3, 2)
```

```
>>> index_two = np.array([[0, 1]])
```

```
>>> index_two.shape
```

```
(1, 2)
```

Broadcast index1 against index2:

```
(3, 2) # shape of index_one
```

```
(1, 2) # shape of index_two
```

```
-----
```

```
(3, 2)
```

The shape of `x[5:10, index_one, :, index_two]` is

```
(3, 2, 5, 16)
```

Jack's Dilemma

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

Broadcasting

Fancy Indexing

- Introduction
- Output shape of an indexing op
- Output shape of an indexing op (cont'd)
- Output shape of an indexing op (cont'd)
- Output shape of an indexing op (cont'd)
- **Jack's Dilemma**
- Jack's Dilemma (cont'd)
- Test setup for Jack's problem
- Solving Jack's problem
- Solution verification

The `__array_interface__`

Discussion, questions & exercises

Indexing and broadcasting are intertwined, as we'll see in the following example. One of my favourites from the NumPy mailing list:

```
Date: Wed, 16 Jul 2008 16:45:37 -0500
From: <Jack.Cook@>
To: <numpy-discussion@scipy.org>
Subject: Numpy Advanced Indexing Question
```

Greetings,

I have an I,J,K 3D volume of amplitude values at regularly sampled time intervals. I have an I,J 2D slice which contains a time (K) value at each I, J location. What I would like to do is extract a subvolume at a constant +/- K window around the slice. Is there an easy way to do this using advanced indexing or some other method?

Thanks in advanced for your help.

- Jack

Jack's Dilemma (cont'd)

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays


Broadcasting

Fancy Indexing

- Introduction
- Output shape of an indexing op
- Output shape of an indexing op (cont'd)
- Output shape of an indexing op (cont'd)
- Output shape of an indexing op (cont'd)
- Jack's Dilemma
- **Jack's Dilemma (cont'd)**
- Test setup for Jack's problem
- Solving Jack's problem
- Solution verification

The `__array_interface__`

Discussion, questions & exercises



Test setup for Jack's problem

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

Broadcasting

Fancy Indexing

- Introduction
- Output shape of an indexing op
- Output shape of an indexing op (cont'd)
- Output shape of an indexing op (cont'd)
- Output shape of an indexing op (cont'd)
- Jack's Dilemma
- Jack's Dilemma (cont'd)
- **Test setup for Jack's problem**
- Solving Jack's problem
- Solution verification

The `__array__` interface

Discussion, questions & exercises

```
>>> ni, nj, nk = (10, 15, 20)
```

```
# Make a fake data block such that block[i,j,k] == k for all i,j,k.
```

```
>>> block = np.empty((ni, nj, nk), dtype=int)
```

```
>>> block[:, :, :] = np.arange(nk)[np.newaxis, np.newaxis, :]
```

```
# Pick out a random fake horizon in k.
```

```
>>> k = np.random.randint(5, 15, size=(ni, nj))
```

```
>>> k
```

```
array([[ 6,  9, 11, 10,  9, 10,  8, 13, 10, 12, 13,  9, 12,  5,  6],
       [ 7,  9,  6, 14, 11,  8, 12,  7, 12,  9,  7,  9,  8, 10, 13],
       [10, 14,  9, 13, 12, 11, 13,  6, 11,  9, 14, 12,  6,  8, 12],
       [ 5, 11,  8, 14, 10, 10, 10,  9, 10,  5,  7, 11,  9, 13,  8],
       [ 7,  8,  8,  5, 13,  9, 11, 13, 13, 12, 13, 11, 12,  5, 11],
       [11,  9, 13, 14,  6,  7,  6, 14, 10,  6,  8, 14, 14, 14, 14],
       [10, 12,  6,  7,  8,  6, 10,  9, 13,  6, 14, 10, 12, 10, 10],
       [10, 12, 10,  9, 11, 14,  9,  6,  7, 13,  6, 11,  8, 11,  8],
       [13, 14,  7, 14,  6, 14,  6,  8, 14,  7, 14, 12,  8,  5, 10],
       [13,  5,  9,  7,  5,  9, 13, 10, 13,  7,  7,  9, 14, 13, 11]])
```

```
>>> half_width = 3
```

Solving Jack's problem

- Tutorial layout

- Num-What?

- Setup

The NumPy ndarray

Structured arrays

Broadcasting

Fancy Indexing

- Introduction

- Output shape of an indexing op

- Output shape of an indexing op (cont'd)

- Output shape of an indexing op (cont'd)

- Output shape of an indexing op (cont'd)

- Jack's Dilemma

- Jack's Dilemma (cont'd)

- Test setup for Jack's problem

- Solving Jack's problem

- Solution verification

The `__array_interface__`

Discussion, questions & exercises

```
# These two indices ensure that we take a slice at each (i, j) position
```

```
>>> idx_i = np.arange(ni)[: , np.newaxis, np.newaxis]
```

```
>>> idx_j = np.arange(nj)[np.newaxis, :, np.newaxis]
```

```
# This is the substantive part that picks out the window
```

```
>>> idx_k = k[:, :, np.newaxis] + \
```

```
...         np.arange(-half_width, half_width+1) # (10, 15, 7)
```

```
>>> block[idx_i, idx_j, idx_k] # slice!
```

Applying the broadcasting rules:

```
(ni, 1, 1 ) # idx_i
```

```
(1 , nj, 1 ) # idx_j
```

```
(ni, nj, 2*half_width + 1 ) # idx_k
```

```
-----
```

```
(ni, nj, 7) <-- this is what we wanted!
```

Solution verification

- Tutorial layout

- Num-What?

- Setup

The NumPy ndarray

Structured arrays

Broadcasting

Fancy Indexing

- Introduction

- Output shape of an indexing op

- Output shape of an indexing op (cont'd)

- Output shape of an indexing op (cont'd)

- Output shape of an indexing op (cont'd)

- Jack's Dilemma

- Jack's Dilemma (cont'd)

- Test setup for Jack's problem

- Solving Jack's problem

- **Solution verification**

The `__array_interface__`

Discussion, questions & exercises

```
>>> slices = cube[idx_i, idx_j, idx_k]
```

```
>>> slices.shape
```

```
(10, 15, 7)
```

```
# Now verify that our window is centered on k everywhere:
```

```
>>> slices[:, :, 3]
```

```
array([[ 6,  9, 11, 10,  9, 10,  8, 13, 10, 12, 13,  9, 12,  5,  6],
       [ 7,  9,  6, 14, 11,  8, 12,  7, 12,  9,  7,  9,  8, 10, 13],
       [10, 14,  9, 13, 12, 11, 13,  6, 11,  9, 14, 12,  6,  8, 12],
       [ 5, 11,  8, 14, 10, 10, 10,  9, 10,  5,  7, 11,  9, 13,  8],
       [ 7,  8,  8,  5, 13,  9, 11, 13, 13, 12, 13, 11, 12,  5, 11],
       [11,  9, 13, 14,  6,  7,  6, 14, 10,  6,  8, 14, 14, 14, 14],
       [10, 12,  6,  7,  8,  6, 10,  9, 13,  6, 14, 10, 12, 10, 10],
       [10, 12, 10,  9, 11, 14,  9,  6,  7, 13,  6, 11,  8, 11,  8],
       [13, 14,  7, 14,  6, 14,  6,  8, 14,  7, 14, 12,  8,  5, 10],
       [13,  5,  9,  7,  5,  9, 13, 10, 13,  7,  7,  9, 14, 13, 11]])
```

```
>>> (slices[:, :, 3] == k).all()
```

```
True
```

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

Broadcasting

Fancy Indexing

The `__array_interface__`

- Array interface overview

Discussion, questions & exercises

The `__array_interface__`

Array interface overview

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

Broadcasting

Fancy Indexing

The `__array_interface__`

- **Array interface overview**

Discussion, questions & exercises

Any object that exposes a suitable dictionary named `__array_interface__` may be converted to a NumPy array. This is very handy for exchanging data with other libraries (e.g., PIL \leftrightarrow SciPy). The array interface has the following important keys (see <http://docs.scipy.org/doc/numpy/reference/arrays.interface>

- **shape**
- **typestr**: see above URL for valid typecodes
- **data**: (20495857, True); 2-tuple—pointer to data and boolean to indicate whether memory is read-only
- **strides**
- **version**: 3

- Tutorial layout
- Num-What?
- Setup

The NumPy ndarray

Structured arrays

Broadcasting

Fancy Indexing

The `__array_interface__`

Discussion, questions &
exercises

Discussion, questions & exercises